



Kinox - KUF Urinal With Concealed Sensor (Battery Operated)

Voltage	: 0.6V (DC)
Power Consumption	: 0.5mW (DC)
Battery	: 4 X AA Duracell Alkaline Battery
Water Pressure	: 0.05 Mpa - 0.7 Mpa
Detection Zone	: 30 - 90 cm
Ambient Temperature	: 0.1 ~ 45°C
Diameter of Inlet/Outlet Pipe	: G (1/2")
Degree of Protection	: IP 56
Dimensions	: 680 X 290 X 345 mm



EU 01 Automatic Urinal Flusher (Touch Free Operation)

Voltage	: 220V / 50 Hz (AC), 0.6V (DC)
Power Consumption	: < 2 W (AC), 0.5mW (DC)
Battery	: 4 X AA Duracell Alkaline Battery
Water Pressure	: 0.05 Mpa - 0.7 MPa
Detection Zone	: 60 cm
Ambient Temperature	: 0.1 ~ 45°C
Diameter of Inlet/Outlet Pipe	: G (1/2")
Degree of Protection	: IP 56
Dimensions	: 128 X 128 mm

*** Available in
 DC (Battery) Model: EU 01
 AC (Electrical) Model: EU 03 E
 AC / DC (Electrical + Battery) Model: EU 04BE
 Usage: With 4AA alkaline batteries it can be used for about 1 year worked for 150 cycles a day

EU 020 Exposed Urinal Flusher (Touch Free Operation)

Voltage	: 220V / 50 Hz (AC), 0.6V (DC)
Power Consumption	: < 2 W (AC), 0.5mW (DC)
Battery	: 4 X AA Duracell Alkaline Battery
Water Pressure	: 0.1 Mpa - 0.6 MPa
Detection Zone	: 60 cm
Ambient Temperature	: 0 ~ 40°C
Diameter of Inlet/Outlet Pipe	: G (1/2")
Degree of Protection	: IP 56

Usage: With 4AA alkaline batteries it can be used for about 1 year worked for 150 cycles a day

